V7 L17EM

LCD Specification	17" Hydis panel
Viewable size	338 mm x 270 mm
Pixel pitch	0.264 mm x 0.264 mm
Contrast	430:1
Brightness	250 cd/m²
Response time	20/10
maximum resolution	1280 x 1024
recommended resolution	1280 x 1024
Colours	16.7 Mio.
Horizontal frequency	60 kHz
Vertical frequency	56 - 75 Hz
Adjustment	Auto-Configuration, H/V Position, H/V Size, R/G/B gain, OSD position, language etc.
Resolution	640 x 480 @ 75 Hz
	800 x 600 @ 75 Hz
	1024 x 768 @ 75 Hz
	1280 x 1024 @ 75 Hz
Features	speakers, headphone jack, wallmountable, Kensington-lock, beige design
Plug & Play	DDC2B
Signal input	15 pin D-Sub
Power management	VESA, DPMS
Power consumption	on: 40; suspend: 3; standby: 3; off: 3
Standards	TCO 99, CE, D, S, FI, N, TÜV/GS, ISO 13406-2
Pixel criteria	dark <= 3; bright <= 3; subpixel total <= 7
Monitor dimension (W x H x D)	411 x 411.5 x 190 mm
Monitor weight	5.1 kg; 7.0 kg incl. packing
Warranty	3 years onsite service
Supply	5 language user's manual, power cable, driver disk, VGA cable, AC/DC cable, Audio cable

Subject to alteration